



# GN 741


## Plugs



GN 741-OS



GN 741-ES



GN 741-AS

american unit  
metric unit

Elesa-Gantergriff		Main dimensions							Weight	
Code	Description	d <sub>1</sub>	A	B	D	d	l	s	lbs	g
GN.37811	GN 741-22-M16x1.5-OS-1	- M16x1.5	0.31 8	0.3 7.5	0.87 22	- M5	0.31 8	0.71 18	0.022	10
GN.37813	GN 741-26-M20x1.5-OS-1	- M20x1.5	0.33 8.5	0.3 7.5	1.02 26	- M5	0.31 8	0.83 21	0.066	30
GN.37816	GN 741-32-M26x1.5-OS-1	- M26x1.5	0.35 9	0.31 8	1.26 32	- M5	0.31 8	1.06 27	0.11	50

american unit  
metric unit

Elesa-Gantergriff		Main dimensions							Weight	
Code	Description	d <sub>1</sub>	A	B	D	d	l	s	lbs	g
GN.37821	GN 741-22-G3/8-OS-1	- G 3/8	0.31 8	0.3 7.5	0.87 22	- M5	0.31 8	0.71 18	0.051	23
GN.37822	GN 741-26-G1/2-OS-1	- G 1/2	0.33 8.5	0.3 7.5	1.02 26	- M5	0.31 8	0.83 21	0.07	32
GN.37823	GN 741-32-G3/4-OS-1	- G 3/4	0.35 9	0.31 8	1.26 32	- M5	0.31 8	1.06 27	0.11	50
GN.37824	GN 741-40-G1-OS-1	- G 1	0.43 11	0.33 8.5	1.57 40	- M5	0.31 8	1.26 32	0.194	88

#### Material

Aluminium, sandblasted matte finish.

#### Flat packing ring

NBR synthetic rubber.

#### Maximum continuous working temperature

250°F (120°C).

#### *Special executions on request (For sufficient quantities)*

- Execution AS: plugs with laser engraved graphic symbol "drain", according to DIN regulations.
- Execution ES: plugs with laser engraved graphic symbol "fill", according to DIN regulations.
- Plugs with DIA= 0.08 (2 mm) side breather hole.

#### *Features*

GN 741 plugs are provided with a threaded blind hole for assembling a dipstick.



---

**elesa**

STANDARD MACHINE ELEMENTS WORLDWIDE