


GN 743.1

Oil level indicators for application with high temperatures

elesa

+350°F
-5°F
METRIC
BSP



american unit
metric unit

Elesa-Gantergriff				Main dimensions						Weight
Code	Description	Code	Description	d ₁	A	B	D	d	s	lbs g
GN.37701	GN 743.1-11-M16x1.5-A	GN.37731	GN 743.1-11-M16x1.5-B	- M16x1.5	0.31 8	0.3 7.5	0.87 22	0.43 11	0.79 20	0.018 8
GN.37703	GN 743.1-14-M20x1.5-A	GN.37733	GN 743.1-14-M20x1.5-B	- M20x1.5	0.33 8.5	0.3 7.5	1.02 26	0.55 14	0.91 23	0.022 10
GN.37705	GN 743.1-18-M26x1.5-A	GN.37735	GN 743.1-18-M26x1.5-B	- M26x1.5	0.35 9	0.31 8	1.26 32	0.71 18	1.18 30	0.04 18
GN.37707	GN 743.1-18-M27x1.5-A	GN.37737	GN 743.1-18-M27x1.5-B	- M27x1.5	0.35 9	0.31 8	1.26 32	0.71 18	1.18 30	0.04 18
GN.37709	GN 743.1-24-M33x1.5-A	GN.37739	GN 743.1-24-M33x1.5-B	- M33x1.5	0.43 11	0.33 8.5	1.57 40	0.94 24	1.42 36	0.057 26
GN.37711	GN 743.1-32-M40x1.5-A	GN.37741	GN 743.1-32-M40x1.5-B	- M40x1.5	0.47 12	0.35 9	1.97 50	1.26 32	1.81 46	0.086 39
GN.37713	GN 743.1-32-M42x1.5-A	GN.37743	GN 743.1-32-M42x1.5-B	- M42x1.5	0.47 12	0.35 9	1.97 50	1.26 32	1.81 46	0.095 43
GN.37715	GN 743.1-11-G3/8-A	GN.37745	GN 743.1-11-G3/8-B	- G 3/8	0.31 8	0.3 7.5	0.87 22	0.43 11	0.79 20	0.02 9
GN.37717	GN 743.1-14-G1/2-A	GN.37747	GN 743.1-14-G1/2-B	- G 1/2	0.33 8.5	0.3 7.5	1.02 26	0.55 14	0.91 23	0.024 11
GN.37719	GN 743.1-18-G3/4-A	GN.37749	GN 743.1-18-G3/4-B	- G 3/4	0.35 9	0.31 8	1.26 32	0.71 18	1.18 30	0.04 18
GN.37721	GN 743.1-24-G1-A	GN.37751	GN 743.1-24-G1-B	- G 1	0.43 11	0.33 8.5	1.57 40	0.94 24	1.42 36	0.057 26
GN.37723	GN 743.1-32-G1 1/4-A	GN.37753	GN 743.1-32-G1 1/4-B	- G 1 1/4	0.47 12	0.35 9	1.97 50	1.26 32	1.81 46	0.093 42

Material

Aluminium, glossy finish.

- Execution A: with technopolymer contrast screen.
- Execution B: without contrast screen.

Window
ESG glass.

Flat packing ring
FKM (type VITON®, registered trade mark of DuPont Dow Elastomers).

Maximum continuous working temperature
350°F (180°C).

Accessories on request

Brass nut type [GH](#), for fitting to reservoirs with wall thickness smaller than 0.20" (5 mm).

Features and applications

GN 743.1 oil level indicators can be used on pressurised oil tanks (oil-proof resistance data available on request). The natural glass window is resistant to scratches.

The seal between the aluminium body and the glass window is guaranteed by an O-ring in FKM (type VITON®, registered trade mark of DuPont Dow Elastomers).



STANDARD MACHINE ELEMENTS WORLDWIDE